





CABLE


STAINLESS STEEL T316


1 x 19	Diameter in Inches	Net Price Per Foot	Nominal Breaking Strength - Lbs	Approx. Wt./1000'	Diameter in Inches
	1/16		466	9	1/16
	3/32		1,050	19	3/32
	1/8		1,866	35	1/8
	5/32		2,908	55	5/32
	3/16		4,200	77	3/16
	7/32		5,728	102	7/32
	1/4		7,481	135	1/4
	9/32		9,400	170	9/32
	5/16		11,676	210	5/16
	3/8		15,575	300	3/8
	7/16		20,000	410	7/16
	1/2		26,675	521	1/2
	9/16		32,400	670	9/16
5/8		42,000	855	5/8	

7 X 7	Diameter in Inches	Net Price Per Foot	Nominal Breaking Strength- Lbs.	Approx. Wt./ 1000'	Diameter in Inches
	3/64		188	4.0	3/64
	1/16		335	7.3	1/16
	5/64		500	11.4	5/64
	3/32		806	16	3/32
	1/8		1434	29	1/8
	5/32		2211	43	5/32
	3/16		3218	61	3/16
	7/32		4410	83	7/32
	1/4		5728	113	1/4
	9/32		7255	134	9/32
	5/16		8090	171	5/16
	3/8		11,494	243	3/8
	7/16		15,299	342	7/16
1/2		18,232	432	1/2	

CABLE

STAINLESS STEEL T316

7 X 19	Diameter in Inches	Net Price Per Foot	Nominal Breaking Strength- Lbs.	Approx. Wt./ 1000'	Diameter in Inches
	3/32		700	17	3/32
	1/8		1,328	29	1/8
	5/32		2,074	45	5/32
	3/16		2,963	65	3/16
	7/32		4,056	86	7/32
	1/4		5,308	110	1/4
	9/32		6,727	150	9/32
	5/16		8,290	173	5/16
3/8		11,951	243	3/8	

6 X 19 IWRC	7/16		15,000	356	7/16
	1/2		19,300	458	1/2
	9/16		24,300	590	9/16
	5/8		29,800	715	5/8
	3/4		50,000	922	3/4
	7/8		58,000	1430	7/8
	1		80,000	1870	1

Corrosion Resistant Rope Care for Marine Applications

Corrosion Resistant, or "Stainless Steel", rigging and ropes should be rinsed with fresh water on a regular basis. Using a water-soluble detergent will not harm the metal and may make general deck cleaning easier. Parts should be inspected after each use. Cables should be checked for wire breaks, misaligned swage fittings, and corrosion. Also, swaged fittings should be checked for cracks. Any other "stainless" parts can be inspected at the same time. "Stainless steel" can stain and corrode. It is an alloy, but it does still contain Carbon. So if you see extensive discoloration, or "pitting" the parts should be replaced. If a part requires scraping or grinding to remove corrosion it should be removed from service and replaced with new parts. Regular cleaning and inspections will assure the best possible service life for these parts.

Lifeline Care

Lifelines are usually 7x7 construction stainless steel cables coated with vinyl, or PVC, and usually white in color. The special grade of plastic has been engineered to remain durable and attractive after prolonged exposure to sunlight and seawater. Chemical cleaners and kerosene should not be used to clean plastic coated cables. Their use may actually degrade the integrity of the plastic or, in the case of kerosene, may spread the stain to a larger portion of the cable. These cables should be cleaned at the same time as the "bare" cables in the rigging.