




WIRE ROPE

ROTATION RESISTANT

19X7 Stainless Steel T302/304

19x7	Diameter (inches)	Price (\$/ Foot)	Nominal Break Strength - Lbs	Approximate Weight (Lbs./ ft.)	Diameter (inches)
	1/8		1500	.029	1/8
	5/32		2160	.045	5/32
	3/16		3330	.065	3/16
	7/32		4500	.086	7/32
	1/4		5760	.110	1/4
	5/16		8100	.173	5/16
	3/8		10,800	.243	3/8
	7/16		13,800	.356	7/16
	1/2		20,520	.458	1/2
	9/16		24,200	.590	9/16
	5/8		31,500	.715	5/8

ADDITIONAL CHARGES-

- ☐ 5% for cut lengths 100-499 feet
- ☐ 10% for cut lengths less than 100 feet
- ☐ 10% for any floor measured length

Rotation Resistant Ropes

Rotation resistant ropes are a special category (class) of wire rope designed to resist the tendency to spin or rotate under load. In general these ropes are used as single part lines, or in situations where operating conditions require a rope that will resist cabling in a multipart system. The essential nature of rotation resistant rope designs impose certain limitations on their application and necessitate special handling requirements not encountered with other rope classifications.

19x7 is a multi-strand rope consisting of two strand layers closed in opposing directions. Torsional forces generated by each layer of the rope counteract one another to minimize rotation.

Open swivels are not recommended for use with 19x7 ropes. *

* - Wire Rope Users Manual, Third Edition, Copyright 1993, Wire Rope Technical Board