


THIMBLES

ZINC PLATED/ GALV
AN Style/ Light Duty/
Regular Duty

| AN/ Light Duty Thimbles, Zinc Plated | | | | | | | |
|---|--------------|----------|----------|----------|----------|----------|----------------|
| Size | Style | A | B | C | D | E | \$/1000 |
| 3/64-1/16-5/64 | AN Type | .350 | .703 | .188 | .094 | .032 | |
| 3/32-7/64-1/8 | AN Type | .350 | .703 | .219 | .141 | .032 | |
| 5/32 | AN Type | .400 | .797 | .219 | .172 | .032 | |
| 3/16 | AN Type | .500 | 1.000 | .313 | .203 | .032 | |
| 7/32-1/4 | AN Type | .700 | 1.406 | .406 | .266 | .032 | |
| 5/16 | Light Duty | .750 | 1.250 | .250 | .344 | .062 | |
| 3/8 | Light Duty | 1.000 | 1.750 | .281 | .438 | .074 | |



| Regular Duty Wire Rope Thimbles, Galvanized | | | | | | | | | | |
|--|------------------------|-------------------|----------|----------|----------|----------|----------|----------|----------|--------------------|
| Size | Lbs per 100 pcs | Dimensions | | | | | | | | \$/ 100 pcs |
| | | A | B | C | D | E | F | G | H | |
| 1/8 | 3.50 | 1.94 | 1.31 | 1.06 | .69 | .25 | .16 | .05 | .13 | |
| 3/16 | 3.50 | 1.94 | 1.31 | 1.06 | .69 | .31 | .22 | .05 | .13 | |
| 1/4 | 3.50 | 1.94 | .131 | 1.06 | .69 | .38 | .28 | .05 | .13 | |
| 5/16 | 4.00 | 2.13 | 1.5 | 1.25 | .81 | .44 | .34 | .05 | .13 | |
| 3/8 | 6.70 | 2.38 | 1.63 | 1.47 | .94 | .53 | .41 | .06 | .16 | |
| 1/2 | 12.5 | 2.75 | 1.88 | 1.75 | 1.13 | .69 | .53 | .08 | .19 | |
| 5/8 | 34.5 | 3.5 | 2.25 | 2.38 | 1.38 | .91 | .66 | .13 | .34 | |
| 3/4 | 47.1 | 3.75 | 2.50 | 2.69 | 1.63 | 1.08 | .78 | .14 | .34 | |
| 7/8 | 84.6 | 5.00 | 3.50 | 3.19 | 1.88 | 1.27 | .94 | .16 | .44 | |
| 1 | 97.5 | 5.69 | 4.25 | 3.75 | 2.50 | 1.39 | 1.06 | .16 | .41 | |

Conforms to Federal Specification FF-T-276b, Type II